

## **Products**



IX850

**Door Station** 

Touch screen with stainless steel surface



IX821

**Door Station** 

Touch Key with stainless steel surface



IX610

**Door Station** 

Villa/video door bell



IX471

Monitor

Touch screen

# 2Easy-IX IP Intercom System







### PoE

Support Standard PoE (50V) as device power supply, one cable for all.



### Fisheye Camera

170 degree wide angel fisheye camera.



### **IP Camera Integrated**

Support monitor Onvif IP Camera from indoor unit and guard unit.



### **Easy Configure**

Plug and play, auto configure for names/numbers/IP address.

# **Easy Installation**



## Features



### **Self Managed Access**

Add or delete Pin code or proximity access card/Fob without the need for PC management software.



### **Address Book**

Update door-station address book via monitor automatically sync to door station.



#### **IP Camera**


Manage IP cameras connected to the system, switch to camera during a call.



#### **Multi Channels**

Multi channel allow users to have multi conversations in the same time.





# Residential

### **Example Configuration**

Single door station for garage and gate, smart device integration plus additional CCTV cameras to view gate from a different angle. (add up to 16 IP cameras)




32

Maximum 32 monitors



32

Maximum 32 video door bell



# Townhouse with Single & Multi Entrances

### **Example Configuration**

Multi door station for common entry points (e.g garage & gate), plus single door-station for individual Townhouse, smart device integration plus cameras to monitor common areas (e.g gate, pool).



256

Maximum 256 self-config IP Monitors




32

Maximum 32 video door bells for each Townhouse



32

Maximum 32 doors for one complex



# **Apartment Complex**

### **Example Configuration**

Multi blocks, multi common entry doors & gates, concierge desk. Apartment to Apartment calls, smart device integration plus CCTV cameras to monitor common areas...



### 8000

Maximum 8000 Monitors




### 32

Maximum 32 video door bells for each Apt



### 32

Maximum 32 doors for each building or common gate



## IX850

### **Touch Screen Door Station**

Common entry door station, with proximity card/Fob and pin code access for residents.



Fingerprint-proof Stainless steel surface



5 inch TFT display With touch glass screen



Customisable menu options multi language, address book



170° wide angle fisheye camera.



Supports both 13.56Mhz and 125Khz card. Dual car reader







Flush mounting

### IX821

### **Modular Door Station**

Modular design door station with a wide range of functions to select from.

Stainless steel frame, surface or flush mount options.

Add up to 6 modules per door station to meet the exact requirements of any building.



**821-VD**Main camera module



**821-DR**LED display card reader



821-MK

Mechanical keypad



821-S4

Touch sensor call button



821-LB

Backlight info board



821-BM

Blank block



2 Modules Door station Surface/Flush mounting



3 Modules Door station Surface/Flush mounting

## **Indoor Monitor IX471**



7Inch touch screen



### Handset

Support handset accessory



#### Alarm

Maximum 8 alarm zooms







### Transfer

Transfer call to APP.



### Customisable

Logo, Menu, UI.



### **Elevator control**

Support elevator control

# Concierge Station GL471





### **Camera View**

GL471 can display the door station or external CCTV Camera. When calling an apartment, concierge can display/toggle the door station or paired CCTV Camera on apartment monitor.



### **Handset Optional**

GL471 is available with handset or without handset.



#### **Desk Mount**

Wall mount or desk mount options available.



#### Transfer

Transfer calls to mobile APP when apartment is unattended.

## Free PC Software





### **Batch configuration**

Configure all online devices with one click.



### Maintenance

Update configuration, change settings from any device with an internet connection.

### Information

### Basic

#### **Power Source:**

Power-over-Ethernet (IEEE 802.3af Class 0)

**LAN Interface:** 

10 BASE-T / 100 BASE-TX Ethernet (RJ-45)

**Network Protocols:** 

TCP, UDP, SIP, DHCP, AUTOIP, TFTP, RTSP,

RTP, RTCP, IGMP, MLD, NTP, DNS

Media codec:

Audio, G.711; Video, H.264

**Bandwidth Usage:** 

Audio,128Kbps; Video, 24Kbps ~ 8,192Kbps

Communication

Hands-free

Wire Type:

Cat-5e or Cat-6

**Wiring Distance:** 

100m (Approx. 330')

**Operating temperature:** 

-10 to +50 (oC)

### **Device**

#### IX610/IX850:

DC7121 Camera Type 1/3.7" Ultra Sense, ISP

with 77dB WDR

Len angle: 170 degree with Fisheye correction

Minimum illumination: 5 lux

NT99141 Camera Type 1/4" CMOS

Len angle: 90 degree

Minimum illumination: 8 lux

#### **TFT Screen**

TFT Screen (IX471) 7 inch, 800\*480 resolution

TFT Screen (IX850) 5 inch, 480\*800 resolution

### All door stations

Ingress Protection IP65
Impact Protection IK08

### **Dimensions**

